


## IPv6: Internet Protocol version 6

- Why?
- Addressing
- Packet format
- Fragmentation
- Coexistence
- Control messages (ICMPv6)
- Getting an address (DHCPv6, Autoconfig.)
- Finding neighbours (ND)
- Naming things (DNS)

## Why we need IPv6



Obviously, having fewer addresses than people is silly

1

2

## IPv6 in a nutshell

- New version of IP with bigger addresses
- Designed starting in 1994
  - operational experimentally in 1997
- Major deployments starting now
  - US Federal Government requirement in 2008
- Connectionless datagram approach doesn't change
- Will co-exist with IPv4 for many years

## IPv6 Address Format

- In the abstract, it's just a 128 bit binary number
- Conventionally written in “colon-separated hexadecimal:”
 

```
2610:00a0:c779:000b:0000:0000:d1ad:35b4
```

 abbreviated as
 


```
2610:a0:c779:b::d1ad:35b4
```
- Obviously, the routing system has to treat it separately from IPv4

3

4



## IPv6 Header Format



← 32 bits →

credit: Steve Deering

9

## Back to the IPv4 header



← 32 bits →


Green shaded parts have been dropped from IPv6.

credit: Steve Deering

10

## Mapping to Layer 2

- The IP packet has to be sent inside a Layer 2 frame, such as an Ethernet frame.
- The exact way this is done depends on the type of Layer 2 link
  - e.g. using Ethertype 0x86DD on Ethernet



Layer 2

Layer 3

Layer 2

11

## Explanation of IPv6 header

- Version: 6
- Traffic Class Field, identical to DS Field in IPv4
  - 8 bits used to manage quality of service
- Flow Label
  - 20 bits intended for flow-based quality of Service
- Payload length
  - not including header
- Next Header
  - explained below
- Hop Limit
  - Same as IPv4 TTL


Wrong in Shay

12

## Next Header value

- An IPv6 packet can start with a string of headers
  - If there's only the basic header described so far, “Next Header” contains a protocol number just like IPv4, saying that the payload is TCP, UDP, etc.
- Various *optional* additional headers are defined
  - Hop-by-hop options header
  - Destination options header
  - Routing headers (several types)
  - Fragment header
  - and others
- Each one includes a new “Next Header” value
  - The last one is always the payload protocol


## IPv6 Packets with Headers



credit: Steve Deering

## Fragmentation

- IPv6 requires that every link in the Internet has an MTU of 1280 bytes or greater
  - Any link incapable of this must fragment *at link level*
- IPv6 fragmentation is *only* done by the sending host, never by routers
  - Sender must determine path MTU size
- Fragmentation header details based on IPv4 experience



- M=1 for more fragments, M=0 for last fragment
- Res=Reserved

## ICMPv6 and DHCPv6

- We'll skip the details
- They are both similar too but different in detail from the IPv4 versions

## Routing for IPv6

- RIP, OSPF, BGP4 come in IPv6 versions
  - no change in principle
  - known as RIPng, OSPFv6 and BGP4+

## Getting an address without DHCP: IPv6 Stateless Auto-configuration

- Intended for "dentist's office" scenario (i.e. no manual configuration needed)
- Nodes start by acquiring a Link Local address using the FE80::/10 prefix
- Router issues Router Advertisements to provide a routeable prefix for new nodes
  - unique global address formed from that prefix
- Nodes then use Neighbor Discovery and Duplicate Address Detection procedures to find neighbours
  - ARP experience showed that broadcast is not a good approach (risk of "broadcast storms")
  - Therefore, IPv6 uses local multicast for ND

17

## Auto-configuration messages

- Router Solicitation\*
- Router Advertisement\*
- Neighbour Solicitation\*
- Neighbour Advertisement\*
- Redirect

*All sent as ICMPv6 messages.*

*\* May be sent to multicast addresses that don't "wake up" everybody, unlike ARP multicast*

19

## Auto-configuration functions

- Router Discovery
- Prefix Discovery
- Parameter Discovery
- Address Autoconfiguration
- Address Resolution
- Next-hop Determination
- Neighbour Unreachability Detection (NUD)
- Duplicate Address Detection (DAD)
- Redirect: router supplies better first-hop

18

## Forming an address automatically

- Prefix (normally 64 bits)
  - Initially , FE80::/64 (link local)
  - Secondly, prefix received in Router Advertisement
- Interface Identifier (normally 64 bits)
  - Simplest: Ethernet address padded out to 64 bits  
34 56 78 9A BC DE becomes  
3656:78FF:FE9A:BCDE  
(16 bits inserted, and U/L bit inverted)
  - Privacy addresses: choose a pseudo-random value
  - Secure ND: a cryptographically generated value

20

## DNS for IPv6


- A records carry 32-bit IPv4 addresses
- AAAA records carry 128-bit IPv6 addresses
- DNS queries for AAAA records can travel over IPv4 or IPv6
- A modern resolver returns both A and AAAA records

21

## IPv4 and IPv6 coexistence

- The old and new versions will have to live together and work together for many years
- IPv6 can be carried over IPv4 in “tunnels”
  - IPv6 packets encapsulated in IPv4 packets
- Servers and ISPs will become “dual stack,” able to support IPv4 and IPv6 clients simultaneously
- Application proxies will be able to map IPv4 clients to IPv6 servers, or the opposite
- Direct translation of v4 to v6 at packet level doesn't work well

22



23

## References

- Shay 11.3
  - bugs:
    - "priority" and "flow label" out of date on page 562
    - ignore the "registry" bits in Fig.11.20 and page 568.
    - IPv4-compatible format (Fig. 11.22(b)) is obsolete and the whole discussion of that figure is confused.
- IPv6 Essentials by Silvia Hagen
- Lots of RFCs:
  - 2460 (protocol), 4861+4862 (autoconfig), 4291 (addressing), 4294 (node requirements - lists many important RFCs), etc., etc.

24